



UDUPI COCHIN SHIPYARD LIMITED

(Formerly TEBMA Shipyards Limited)
Ministry of Ports, Shipping and Waterways,
Government of India

CONTRACT CELL DEPARTMENT

CORRIGENDUM - 1 Dated: 04-01-2024

Tender No.: UCSL/CC/T/W/003

Sir,

CORRIGENDUM-1 ANNEXURE III-A


The following terms of the subject tender is amended as follows:

1. Annexure III-A Reference Drawing
2. All the other terms and conditions of the tender enquiry remains unchanged.


For Udupi Cochin Shipyard Limited,

Assistant General Manager (Materials & Contract Cell)


सोणि क्लेमेन्ट टी एम
SONY CLEMENT T M
सहायक महाप्रबंधक/ASSISTANT GENERAL MANAGER
उदुपि कोचीन शिपयार्ड लिमिटेड
UDUPI COCHIN SHIPYARD LIMITED
माल्पे, कर्नाटक/MALPE, KARNATAKA-576 108




Looking aft to forward




Looking forward to aft




DETAIL BILGE KEEL SCALE 1:25




DETAIL A




DETAIL INSERT PART



DETAIL B



LOCATION OF BILGE KEEL TYPICAL FRAME



BILGE KEEL ORDINATES

Aft Bilge Keel Ordinates and Angle from Baseline


Frame	h mm	Degrees
50	224	45
55	224	45
60	224	45
65	224	45
70	224	45
85	224	45
90	224	45

NOTES:
- No marked steel to be Grade "A" Mild Steel ($R_m=235 \text{ N/mm}^2$)

For IS Code 2008:
- Bilge keel total projected surface = 8.54 m²
- Projected length on ship (One side) = 28.100 m




COPYRIGHT CONOSHIP INTERNATIONAL B.V. 2009. All rights reserved. This document or any part thereof may not be made public or disclosed, copied or otherwise reproduced or used in any form or by any means, including, but not limited to, use hereof for the design and manufacturing of identical, similar or derived designs, nor identical, similar or derived documents and specifications, without prior written consent of Conoship International B.V., P.O.Box 6029 - GRONINGEN - THE NETHERLANDS					
CONOSHIP INTERNATIONAL					
DRAWING NO. UY165-2051					
DESCRIPTION Bilge keel arrangement					
SCALE 1:150	SIZE A1	YARD NO. UY165	VERSION: 00	SHEET: 1-1	
DRAWN BY: JK	DATE: 14-07-2023	APPROVED BY: IAC	DATE: 14-07-2023		




Raisedquarter deck 8050 ab

Forecastle deck 8920 ab



Accommodation deck 5100 ab

Tween deck 5400 ab




Propulsion room deck 2600 ab


Tanktop 980 ab




Principal Interior Stairs




Principal Exterior Stairs




BRIDGE DECK 15450




VOID DECK 13950




BOAT DECK 11150




Frame 1




Frame 25




Frame 76




Frame 112




1110 off CL PS




Frame 113




Frame 115



Frame 119




Frame 119-120



LIST OF STAIRS						
N°	DECK	LOCATION	No	TYPE	HEIGHT	REMARKS
S4	8050 ab	Raised Quarter deck	2	Interior	8,25 m	Hot dip galvanized
S5	7200 ab	Aftship	2	Interior	8,25 m	Hot dip galvanized
S6	8920 ab	Forecastle deck	2	Interior	7,50 m	Hot dip galvanized
S7	11150 ab	Boat Deck Aftship	1	Interior	4,00 m	Hot dip galvanized
S8	8050 ab	Boat Deck Aftship	1	Interior	4,00 m	Hot dip galvanized
S9	13950 ab	Void Deck	1	Interior	2,50 m	Hot dip galvanized
S10	15450 ab	Bridge Deck	1	Interior	2,50 m	Hot dip galvanized
S11	13950 ab	Bridge Deck	1	Interior	2,50 m	Hot dip galvanized
S12	9500 ab	Raised Quarterdeck / Boat Deck	2	Interior	1400mm+1700mm	Rubber tile covered
S13	8050 ab	Propulsion room Deck	1	Interior	1130 mm	Attention of floor heights
S14	2600 ab	Propulsion room Deck	1	Interior	1130 mm	Rubber tile covered
S15	5250 ab	Accommodation Deck	1	Interior	1530 mm	Attention of floor heights
S16	3580 ab	Accommodation Deck / Raised Quarter Deck	2	Interior	1400mm+1400mm	Rubber tile covered
S17	8050 ab	Accommodation Deck / Raised Quarter Deck	1	Interior	2150 mm	Attention of floor heights
S18	11150 ab	Boat Deck / Void Deck	1	Interior	2150 mm	Rubber tile covered
S19	15450 ab	Void Deck / Bridge Deck (Wheelhouse)	1	Interior	2150 mm	Attention of floor heights



LIST OF LADDERS				
N°	DESCRIPTION	LOCATION	N° of LADDERS	REMARKS
L1	Escape Propulsion Room	Aftship SB	1	Escape
L2	Access Ventilation Duct Hold	Aftship SB	1	
L3	Entrance Hold / Ventilation Duct	Foreship PS	2	Escape
L4	Entrance Steering Gear	Raised Quarterdeck Aftship SB	1	
L5	Entrance Provision Store	Raised Quarterdeck Aftship PS	1	
L6	Entrance Bowthruster Room	Tweendeck Foreship CL	1	
L7	Entrance CO2 Room	Forecastle deck Foreship SB	1	
L8	Access Topdeck	Aftship SB	1	Backrest
L9	Access Boatdeck	Aftship PS	1	Backrest
L10	Entrance Hold / Ventilation Duct	Aftship PS	1	Escape
L11	Access Ventilation Duct	Foreship CL	1	
L12	Entrance Forecastle Store	Foreship	1	
L13	Entrance Forepeak Tank	Foreship	6	See details Fr.119-120
L14	Access Wavebreaker	Foreship	1	
L15	Access Coaming	Midship	4	
L16	Escape Accommodationdeck	Aftship PS	1	Escape
L17	Entrance Fuel Bunker tank PS	Midship PS	2	NOT GALVANISED
L18	Entrance Fuel Bunker tank SB	Midship SB	2	NOT GALVANISED
L19	Access Voiddeck	Aftship PS & SB	2	
L20	Access / Escape Aft Coaming	Aftship, Fr.25	5	Access / Escape
L21	Access Side Tanks SB & PS	Midship, Fr.34 - 97	14	Access
L22	Access Side Tanks SB & PS	Midship, Fr.105	2	Access
L23	Embarkation bulwark SB & PS	Aftship SB & PS	2	
L24	Access Aft mast	Aftship	1	Access

NOTE:
 - Positions and quantity of steps to be determined in Cadmatic
 - After manufacture hot-dip galvanized
 - Ladders in Fuel tanks (L17 and L18) NOT TO BE GALVANISED
 - The backrest for vertical ladders start at a height of 2.050m.




REV	DATE	MADE BY	APPROVED BY	DESCRIPTION
1	25-07-2023	JH	RB	25-07-2023


DRAWING NO. **UY165-3141**
 DESCRIPTION **Ladders and stairs arrangement**
 SCALE: 1:200
 SIZE: A0
 YARD NO. UY165
 VERSION: 00
 SHEET: 1-1
 DRAWN BY: JH
 DATE: 25-07-2023
 APPROVED BY: RB
 DATE: 25-07-2023




SEC. 1 - 1




SEC. 2 - 2




SEC. 3 - 3




SEC. 4 - 4




Detail A




Detail B



Looking forward to aft




Looking aft to forward



REV	DATE	MADE BY	APPROVED BY	DESCRIPTION
01	18-10-2023	IAC	EP	update according Owners' comments
COPYRIGHT CONOSHIP INTERNATIONAL B.V. 2009. All rights reserved. This document or any part thereof may not be made public or disclosed, copied or otherwise reproduced or used in any form or by any means, including, but not limited to, use hereof for the design and manufacturing of identical, similar or derived designs, nor identical, similar or derived documents and specifications, without prior written consent of Conoship International B.V. P.O. Box 6029 - GRONINGEN - THE NETHERLANDS				
DRAWING NO. UY165-2052				
DESCRIPTION Fender Arrangement				
SCALE 1:150	SIZE: A1	YARD NO. UY165	VERSION: 00	SHEET: 1-1
DRAWN BY: JK	DATE: 14-07-2023	APPROVED BY: IAC	DATE: 14-07-2023	

TOP OF BOXCOOLERS 2280 A.B.




fr22 fr24 fr26

TANKTOP 980 A.B.



fr20 fr22 fr24 fr26

FRAME 22




2280

2700

1350

980

FRAME 23



2280

2700

1350

980

PENDING INFORMATION SUPPLIER

Main components Sea Chest (xxxx)

Pos nr.	Quantity	Description	Comp. No.	Make	Type	Capacity.	Weight [kg]
CO-01	1	-	-	-	-	-	-
CO-02	1	-	-	-	-	-	-
CO-03	1	Coolingwaterpump-01	4050-E003	-	-	-	-
CO-04	1	Coolingwaterpump-02	4050-E004	-	-	-	-
CO-05	1	Thermostatic Valve	4050-V009	-	-	-	-

Outfitting Sea Chest (xxxx)

Pos nr.	Quantity	Description	Drawing No.	Comp. No.
Out-01	1	Foundation -	xxxx-xxx	xxxx
Out-02	1	Foundation -	xxxx-xxx	xxxx
Out-03	1	Foundation -	xxxx-xxx	xxxx
Out-04	1	Foundation -	xxxx-xxx	xxxx

NOTES:

- Removable grids made of Grade A steel
- For anodes see: UY165-3181 - Cathodic Protection Plan
- Slit size and amount according supplier recommendations
- Minimum required inlet opening: 0.342 m²
- Minimum required outlet opening: 0.684 dm²
- Removable grids mounted by welding strips or hinges




Box coolers detail PS

Looking SB

SCALE 1:50

LONGITUDINAL VIEW 2700 OFF CL PS



2280

fr20 fr22 fr24 fr26

Actual outlet opening
0.772 m²

Mounting:
Hinged, Removable

Outlet grating

PS
Fore Up


Slit size:
350 x 50mm, R20

Actual inlet opening
0.547 m²


Mounting:
Hinged, Removable

Inlet grating


Slit size:
250 x 50mm, R20



Raised Quarter Deck 8050 above base




Cut B - Welding Detail - Typical Scale 1:4




REFERENCE FILES:

-Sheet CM RD 314 ALU
-810714033 - XXXKVA VOLVO D13MG-KC + LS47.3 M8 + SCR -Haisma Instalho.pdf


Frame 4




Detail insert plate Scale 1:10




Long. section 1200 off C.L. PS




Long. section 1200 off C.L. SB




Long. section 3190 off C.L. SB



Frame 3




Detail Mounting 2 Scale 1:5





NOTES:

- Sections are shown looking forward & port side U.N.O
- Materials
 - No marked steel to be Grade "A" Mild Steel ($\sigma_y=235$ N/mm²)
 - Marked "D". Grade "D" Mild Steel ($\sigma_y=235$ N/mm²)
- Connection between generator sub-frame and skid done by welding, safety factor approx. 3.5 with a3.
- Skid to be fitted with additional weight/ballast to tune the vibration mode to the correction frequency.
- Positioning of ballast pending piping arrangement.
- HEM profile steel grade : S355J2



Cut A - Typical Scale 1:2



Detail mounting 1 Scale 1:10




Bracket - Typical Scale 1:5




Element	Nb	Mass (approx.)
Skid (steel+subframes)	1	(2376+3*469) = 3783 kg
Generator	3	3000 kg
Ballasting	-	1815 kg
Total		13185 kg

REV	DATE	MADE BY	APPROVED BY	DESCRIPTION
COPYRIGHT CONOSHIP INTERNATIONAL B.V. 2009. All rights reserved. This document or any part thereof may not be made public or disclosed, copied or otherwise reproduced or used in any form or by any means, including, but not limited to, use hereof for the design and manufacturing of identical, similar or derived designs, nor identical, similar or derived documents and specifications, without prior written consent of Conoship International B.V., P.O.Box 6029 - GRONINGEN - THE NETHERLANDS				
DRAWING NO. UY165-2076-00 DESCRIPTION Foundation Generator Sets				
SCALE 1:40	SIZE: A1	YARD NO. UY165	VERSION: 00	SHEET: 1-1
DRAWN BY: JK	DATE: 14-07-2023	APPROVED BY: IAC	DATE: 24/04/2023	


Tanktop 980/1090 Ab. BL



Frame 117




Section at C.L.



Long. Section 675 off CL PS

Similar SB



NOTES:

- Sections are shown looking forward & port side.
- Materials:**
- No marked steel to be Grade "A" Mild Steel ($R_m=235 \text{ N/mm}^2$)
- Connection between tunnel and shell plates is pending.
- Bow thruster's ring to be rounded with radius 100mm.

Reference drawings:




UY165-1001-Rev03-General Arrangement Plan
UY165-3040-Rev00-Bowthruster Room Arrangement
UY165-2033-Rev00-Construction plan fore ship

Equipment drawings:

B200E-005-1016-1000-01



REV	DATE	MADE BY	APPROVED BY	DESCRIPTION
CONOSHIP INTERNATIONAL COPYRIGHT CONOSHIP INTERNATIONAL B.V. 2009. All rights reserved. This document or any part thereof may not be made public or disclosed, copied or otherwise reproduced or used in any form or by any means, including, but not limited to, use hereof for the design and manufacturing of identical, similar or derived designs, nor identical, similar or derived documents and specifications, without prior written consent of Conoship International B.V. P.O. Box 6029 - GRONINGEN - THE NETHERLANDS				
DRAWING NO. UY165-2075				
DESCRIPTION Foundation bow thruster				
SCALE	SIZE:	YARD NO.	VERSION:	SHEET:
1:25	A1	UY165	00	1-1
DRAWN BY:	DATE:	APPROVED BY:	DATE:	
CL	14-07-2023	IAC	14-07-2023	



REFERENCE DRAWINGS:

- UY165-3122 - Navigation Lights and Sound Signaling Arrangement
- UY165-3125 - Arrangement Aft Mast

NOTE:

- Type and arrangement of antennas to be arranged by supplier in accordance with Class, Yard and owners requirements







CONOSHIP INTERNATIONAL Copyright CONOSHIP INTERNATIONAL B.V. 2009. All rights reserved. This document or any part thereof may not be made public or disclosed, copied or otherwise reproduced or used in any form or by any means, including, but not limited to, use hereof for the design and manufacturing of identical, similar or derived designs, nor identical, similar or derived documents and specifications, without prior written consent of Conoship International B.V. P.O.Box 6029 - GRONINGEN - THE NETHERLANDS				
DRAWING NO. UY165-3126				
DESCRIPTION Arrangement fore mast				
SCALE	SIZE	YARD NO.	VERSION	SHEET
1:50	A1	UY165	00	1-1
DRAWN BY:	DATE:	APPROVED BY:	DATE:	
JH	12-07-2023	RB	14-07-2023	

REFERENCE DRAWINGS:


- UY165-3122 - Navigation Lights and Sound Signaling Arrangement
- UY165-3126 - Arrangement Fore Mast

NOTE:


- Type and arrangement of antennas to be arranged by supplier in accordance with Class, Yard and owners requirements




DRAWING NO. UY165-3125			
DESCRIPTION Aft Mast Arrangement			
SCALE 1:50	SIZE A3	YARD NO. UY165	VERSION 00
DRAWN BY: JH	DATE: 12-07-2023	APPROVED BY: RB	DATE: 14-07-2023




Outfitting Drip-trays and Gutter-ways Voiddeck		
Pos nr.	Description	Comp. No.
Out-01	Gutter-way Server space	5010
Out-02	Gutter-ways Staircase	2004
Out-03	Gutter-way Cable duct	3003




Outfitting Drip-trays and Gutter-ways Boatdeck		
Pos nr.	Description	Comp. No.
Out-01	Gutter-way Funnel	4009
Out-02	Gutter-ways Staircase	2004
Out-03	Gutter-way Workshop	4003
Out-04	Gutter-way Store / Corridor / Office	4004
Out-05	Gutter-way Vent. duct Gen. room	4002
Out-06	Gutter-way Paint store	4001




Outfitting Drip-trays and Gutter-ways Raised Quarterdeck		
Pos nr.	Description	Comp. No.
Out-01	Gutter-ways Generator Room PS	3001
Out-02	Gutter-way Generator Room Fore	3001
Out-03	Gutter-way SOS-Locker	3008
Out-04	Gutter-ways Changeroom	3014
Out-05	Gutter-ways Staircase	2004
Out-06	Gutter-way Exh. Vent. Prop. Room	3013
Out-07	Drip-tray Bunkerstation Urea	3010
Out-08	Gutter-way Generator Room Aft	3001
Out-09	Gutter-ways Generator Room SB	3001
Out-10	Gutter-way Pipe duct CL	3003
Out-11	Gutter-ways ER Workshop	3002




Outfitting Drip-trays and Gutter-ways Bridgedeck		
Pos nr.	Description	Comp. No.
Out-01	Gutter-way Wheelhouse	4009
Out-02	Gutter-way Cable duct	3003




Outfitting Drip-trays and Gutter-ways Accommodation deck		
Pos nr.	Description	Comp. No.
Out-01	Gutter-ways Steering Gear Room	2003
Out-02	Gutter-ways Galley	2007
Out-03	Gutter-ways Provision Store	2005
Out-04	Gutter-ways Staircase PS	2004
Out-05	Gutter-ways Washroom	2019
Out-06	Gutter-ways outside Hold Access	4017
Out-07	Gutter-ways Staircase SB	2004
Out-08	Gutter-ways Store	2001
Out-09	Gutter-ways outside Exh. Prop. Room	1002
Out-10	Gutter-ways outside Supply Hold Vent.	4018
Out-11	Gutter-way Cable duct	3003



Outfitting Drip-trays and Gutter-ways Tweendeck / Tank Top		
Pos nr.	Description	Comp. No.
Out-01	Drip-tray Sewage Pump	1001
Out-02	Drip-tray Fuel Pumps and Oil Bilge Pump	1001
Out-03	Drip-tray Dirty Oil Pump	1001
Out-04	Drip-tray Oily Bilge Pump	1001
Out-05	Drip-tray Lubrication Oil Pumps	1001




Outfitting Drip-trays below Forecastle deck		
Pos nr.	Description	Comp. No.
Out-01	Gutter-ways Foreship Entrance PS	3023
Out-02	Gutter-way Exh. duct Ventilation Hold	3022
Out-03	Gutter-ways Em. Gen. Room	3024




Outfitting Drip-trays Tweendeck		
Pos nr.	Description	Comp. No.
Out-01	Gutter-ways Foreship PS	2035
Out-02	Gutter-way Exh. Vent. Hold	3022
Out-03	Gutter-way Foreship CL	2035
Out-04	Gutter-way CO2-Room	2030
Out-05	Gutter-ways Escape Hold	2031




COPYRIGHT CONOSHIP INTERNATIONAL B.V. 2009. All rights reserved. This document or any part thereof may not be made public or disclosed, copied or otherwise reproduced or used in any form or by any means, including, but not limited to, use hereof for the design and manufacturing of identical, similar or derived designs, nor identical, similar or derived documents and specifications, without prior written consent of Conoship International B.V., P.O. Box 6029 - GRONINGEN - THE NETHERLANDS					
DRAWING NO. UY165-3004					
DESCRIPTION Arrangement Drip-trays and Gutter-ways					
SCALE 1:100	SIZE A1	YARD NO. UY165	VERSION: 00	SHEET: 1-1	
DRAWN BY: HLH	DATE: 18-07-2023	APPROVED BY: IAC	DATE: 18-07-2023		




BRIDGEDECK 15450




BOAT DECK 11150




WAVEBREAKER 12405




FORECASTLEDECK 8920




TWEENDECK 5400



VOID DECK 13950



RAISED QUATER DECK 8050




INNER HATCHES:									
Deck	Ref. No.	Description	Tightness Type	Coaming	Min. Clear opening	Hole in Plate	Frame	Y (SB +)	Position [1, 2]
Tweendeck 5400 ab	5400-1	Bowthruster room Entrance	Weatherlight	400	900x900	900x900	Fr.118	0	N/A
Forecastledeck 8920 ab	8920-1	Hold Entrance	Gaslight	400	900x700	900x700	Fr.114+100	-1200	N/A
Forecastledeck 8920 ab	8920-2	Forecastle Store Entrance	Weatherlight	400	900x900	900x900	Fr.114+100	-2100	N/A
OUTER HATCHES:									
Deck	Ref. No.	Description	Tightness Type	Coaming	Min. Clear opening	Hole in Plate	Frame	Y (SB +)	Position [1, 2]
Raised quarter deck 8050 ab	8050-1	Accommodation Escape	Weatherlight	600	800x800	800x800	Fr.23+300	-1750	1
Raised quarter deck 8050 ab	8050-2	Propulsion room Escape	Weatherlight	600	800x800	800x800	Fr.23+300	1260	1
Raised quarter deck 8050 ab	8050-3	Provision store Escape	Weatherlight	600	1300x900	1300x900	FR.0	-4020	1
Raised quarter deck 8050 ab	8050-4	Steering gear room Entrance	Weatherlight	600	800x800	800x800	FR.0	1160	1
Raised quarter deck 8050 ab	8050-7	Bunkerstation	Weatherlight	600	1050x600	1050x600	Fr.23+300	-2885	1
Maindeck 7200 ab	7200-1	Junctionbox Gantry Crane	Weatherlight	350	650x500	N/A	Fr.71-87	5656	1
Voiddeck 13950 ab	13950-1	Entrance Voiddeck, PS	Weatherlight	TBD	TBD	794x1200	Fr.5	TBD	1
Voiddeck 13950 ab	13950-2	Entrance Voiddeck, SB	Weatherlight	TBD	TBD	794x1200	Fr.5	TBD	1
Wavebreaker 12405 ab	12405-1	Drum Hatch Wavebreaker, PS	Weatherlight	N/A	800x800	800x800	Fr.113+445	-1525	2
VENTILATION HATCHES:									
Deck	Ref. No.	Description	Tightness Type	Coaming	Clear opening	Hole in Plate	Frame	Y (SB +)	Position [1, 2, 3]
Raised quarter deck 8050 ab	8050-5	Hold Supply PS	Weatherlight	2290	1155x750	1200x795	Fr.23	-4950	1
Raised quarter deck 8050 ab	8050-6	Hold Supply SB	Weatherlight	2290	1155x750	1200x795	Fr.23	4950	1
Raised quarter deck 8050 ab	8050-8	Supply Propulsion Room	Weatherlight	960	550x650	600x700	Fr.24-100	2080	1
Forecastledeck 8920 ab	8920-3	Hold Exhaust PS	Weatherlight	1080	TBD	900x900	Fr.112+400	-550	1
Forecastledeck 8920 ab	8920-4	Hold Exhaust SB	Weatherlight	1080	TBD	900x900	Fr.112+400	550	1
Forecastledeck 8920 ab	8920-5	Exhaust Emergency Generator	Weatherlight	1080	TBD	900x900	Fr.112+400	1507	1
Forecastledeck 8920 ab	8920-6	Supply Em. Generator PS	Weatherlight	1200	TBD	400x800	Fr.112+400	3713	1
Forecastledeck 8920 ab	8920-7	Supply Em. Generator SB	Weatherlight	1200	TBD	400x800	Fr.112+400	4388	1
Forecastledeck 8920 ab	8920-8	Entrance CO2 Room	Weatherlight	1110	835x750	880x787	Fr.115+300	3791	1
Boatdeck 11150 ab	11150-3	Generator Room Supply	Weatherlight	3060	TBD	1650x1450	Fr.6	4670	2
Boatdeck 11150 ab	11150-4	Propulsion Room Exhaust	Weatherlight	4000	TBD	700x600	Fr.1	CL	2
Bridgedeck 15450 ab	15450-1	Generator Room Exhaust, PS	Weatherlight	TBD	TBD	1352x1315	~Fr.2	-775	3

MAIN PARTICULARS		
Length over all	abl.	89.43 m
Length between perpendiculars	abl.	84.18 m
Breadth moulded	abl.	13.20 m
Depth moulded to maindeck	abl.	7.20 m
Design draught	abl.	4.30 m
Max. draught	abl.	5.25 m
Deadweight at T(max)	abl.	3800 ton
Cargo Hold	abl.	5550 m ³
	abl.	195996 ccbt


Class : BV
Notation : **HULL** *MACH *AUT-JMS
Unrestricted Navigation
- General Cargo Ship
- Heavy Cargo (150kN/m²) complete tanktop
- STRENGTH BOTTOM
- MON-SHAFT
- INWATERSURVEY
Flag Authority : Dutch

REV	DATE	MADE BY	APPROVED BY	DESCRIPTION
1	25-07-2023	JH	RB	Arrangement Small Hatches and Ventilation Openings
DRAWING NO. UY165-3142				
DESCRIPTION				
Arrangement Small Hatches and Ventilation Openings				
SCALE	SIZE	YARD NO.	VERSION	SHEET
1:100	A0	UY165	00	1-1
DRAWN BY:	DATE:	APPROVED BY:	DATE:	
JH	25-07-2023	RB	25-07-2023	


Section 8920 above base




Section A-A




Section B-B




Frame 118




Long. section 1350 off C.L. SB




Long. section 675 off C.L. PS




Long. section 675 off C.L. SB




STUD LINK CHAIN COMPONENTS




HHP ANCHOR
TYPE POOL TW BALANCED




Anchor Lifting Arrangement



Profile View



Anchor Stowage Example



NOTE:
FINAL DIMENSIONS ANCHOR PENDING SUPPLIER INFORMATION

EQUIPMENT INFORMATION
ANCHORS

- EQUIPMENT NUMBER= 670
- 2 X STOCKLESS BOWER ANCHORS OF 1575kg EACH.
- TYPE HHP POOL-TW-BALANCED EXECUTION, HIGH TENSILE STEEL SL52.3 N.
- 440m CHAIN Ø 36mm-GRADE U3.

MAIN PARTICULARS		
Length over all	abt.	89.43 m
Length between perpendiculars	abt.	84.15 m
Breadth moulded	abt.	13.20 m
Depth moulded to maindeck	abt.	7.20 m
Design draught	abt.	4.30 m
Max. draught	abt.	5.25 m
Deadweight at T(max)	abt.	3500 ton
Cargo Hold	abt.	5550 m³
	abt.	195996 cbft

Class : BV
Notation :
- HULL - MACH - AUT-UMS
Unrestricted Navigation
- General Cargo Ship
- Heavy Cargo (150kN/m²) complete tanktop
- STRENGTH BOTTOM
- MON-SHAFT
- INWATERSURVEY
Flag Authority: Dutch

COPYRIGHT CONOSHIP INTERNATIONAL B.V. 2019 All rights reserved. This document or any part thereof may not be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or by any information storage and retrieval system, without prior written permission of CONOSHIP INTERNATIONAL B.V. P.O. Box 4225 - GORINGEN - THE NETHERLANDS		
DRAWING NO.	UY165-3153	
DESCRIPTION	Anchor pocket arrangement, incl. hawse pipe and chain locker	
SCALE	1:50	SHEET: 1-2
DRAWN BY:	DATE:	APPROVED BY:
JH	31-06-2023	IAC 31-06-2023

ACCORDING TO EQUIPMENT NUMBER CALCULATION:

EN = 669
(ACCORDING TO IACS REQUIREMENTS FOR MOORING, ANCHORING AND TOWING)

CHAINLENGTH = 440 m (= 16 cables of 27,5 m)
CHAINDIAMETER = 36 mm
CHAINQUALITY = U3

HAWSEPIPE:

OUTSIDE DIAMETER = 419 mm
WALL THICKNESS = 20 mm

CHAINPIPE:

A = OUTSIDE DIAMETER = 219 mm
t = WALL THICKNESS = 12.5 mm

CHAINLOCKER:

V = SELECTED VOLUME = 3.12 m³

G = FLOOR WIDTH = 1.340 m
L = FLOOR LENGTH = 1.180 m
AREA = FLOOR AREA CHAIN LOCKER = 1.581 m²

EFF. FACTOR = 1.00
EFF. FLOOR AREA IN CHAIN LOCKER = 1.581 m²

H = CHAIN HEIGHT = VOLUME / AREA = 3.12 / 1.581 = 1.97 m

F = FREE HEIGHT (MIN.1.2 M) = 1.35 m

RECOMMENDED HEIGHT OF CHAIN LOCKER (INC. FREE HEIGHT) = 3.62 m

TOTAL MINIMUM CHAIN LOCKER HEIGHT:
MUD BOX + CHAIN HEIGHT + FREE HEIGHT + CHAIN INLET
= M + H + F + CI
= 0.3 + 1.97 + 1.35 + 0.2 = 3.82 m

